



P1 (kW)		iges	n2 (rpm)	M2 (Nm)	fs	Pt (20°C) (kW)	Pt (40°C) (kW)	Motor IE2	FR (kN)					~ Kg													
									MC	MS	PC	PS	CPC	M...	P...	F	FS	CPC									
11.00	PL 25003	317.2	8.8	10694	1.4	20.0	14.0	160M2B	47.3	71.9	-	-	35.4	316	-	280	288	377	476-489								
		262.8	10.7	8860	1.6				45.0	68.5	-	-	33.8														
		226.6	12.4	7640	1.8				45.0	68.5	-	-	33.8														
		218.7	12.8	7373	2.4				42.3	64.4	-	-	31.7														
		188.5	14.9	6355	2.8				42.3	64.4	-	-	31.7														
		167.0	16.8	5630	3.0				42.3	64.4	-	-	31.7														
	PL 18003	149.1	6.0	15639	0.9	17.0	11.9	160L6B	36.0	63.6	84.0	111.6	27.0	265	292	234	270	315	452-469								
		128.4	7.0	13468	1.0				34.5	61.0	80.5	107.0	25.9														
		106.7	8.4	11192	1.3				33.0	58.3	77.0	102.3	24.8														
		94.5	9.5	9912	1.4				30.0	53.0	70.0	93.0	22.5														
		81.4	11.1	8538	1.6				30.0	53.0	70.0	93.0	22.5														
		73.3	12.3	7688	1.8				30.0	53.0	70.0	93.0	22.5														
PL 18003	180.2	7.8	12151	1.1	17.0	11.9	160M4B	33.0	58.3	77.0	102.3	24.8	243	270	212	248	293	452-469									
	149.1	9.4	10054	1.2				31.5	55.7	73.5	97.7	23.6															
	128.4	10.9	8658	1.4				30.0	53.0	70.0	93.0	22.5															
	106.7	13.1	7195	1.9				29.1	51.4	67.9	90.2	21.8															
	94.5	14.8	6372	2.1				28.2	49.8	65.8	87.4	21.2															
	81.4	17.2	5489	2.4				26.7	47.2	62.3	82.8	20.0															
PL 18003	180.2	15.5	6075	1.9	17.0	11.9	160M2B	28.2	49.8	65.8	87.4	21.2	236	263	205	241	286	452-469									
	149.1	18.8	5027	2.2				24.9	44.0	58.1	77.2	18.7															
	128.4	21.8	4329	2.5				24.9	44.0	58.1	77.2	18.7															
	195.3	7.2	13169	0.8				15.0	10.5	160M4B	34.5	61.0							80.5	107.0	25.9	230	257	198	235	280	428-445
	188.2	7.4	12690	0.8							34.5	61.0							80.5	107.0	25.9						
	155.9	9.0	10512	0.9							31.5	55.7							73.5	97.7	23.6						
144.0	9.7	9710	1.0	30.0	53.0	70.0	93.0				22.5																
129.4	10.8	8725	1.1	30.0	53.0	70.0	93.0				22.5																
124.0	11.3	8361	1.5	30.0	53.0	70.0	93.0				22.5																
PL 16003	118.5	11.8	7990	1.1	15.0	10.5	160L6B	30.0	53.0	70.0	93.0	22.5	252	279	220	257	302	428-445									
	109.3	12.8	7370	1.6				29.1	51.4	67.9	90.2	21.8															
	94.9	14.8	6399	1.8				28.2	49.8	65.8	87.4	21.2															
	82.1	17.1	5536	2.3				26.7	47.2	62.3	82.8	20.0															
	75.2	18.6	5071	2.5				26.7	47.2	62.3	82.8	20.0															
	62.9	22.3	4241	2.9				24.0	42.4	56.0	74.4	18.0															
PL 16003	124.0	7.3	13006	1.0	15.0	10.5	160L6B	34.5	61.0	80.5	107.0	25.9	252	279	220	257	302	428-445									
	118.5	7.6	12430	0.8				33.0	58.3	77.0	102.3	24.8															
	109.3	8.2	11465	1.1				33.0	58.3	77.0	102.3	24.8															
	94.9	9.5	9954	1.3				31.5	55.7	73.5	97.7	23.6															
	82.1	11.0	8611	1.6				30.0	53.0	70.0	93.0	22.5															
	75.2	12.0	7888	1.7				30.0	53.0	70.0	93.0	22.5															
PL 16003	274.1	10.2	9241	1.0	15.0	10.5	160M2B	30.0	53.0	70.0	93.0	22.5	223	250	191	228	273	428-445									
	235.4	11.9	7936	0.9				30.0	53.0	70.0	93.0	22.5															
	226.8	12.3	7647	1.2				30.0	53.0	70.0	93.0	22.5															
	209.7	13.4	7070	1.0				28.2	49.8	65.8	87.4	21.2															
	195.3	14.3	6584	1.4				28.2	49.8	65.8	87.4	21.2															
	188.2	14.9	6345	1.4				28.2	49.8	65.8	87.4	21.2															
	155.9	18.0	5256	1.6				24.9	44.0	58.1	77.2	18.7															
	144.0	19.4	4855	1.7				24.9	44.0	58.1	77.2	18.7															
	129.4	21.6	4363	1.9				24.9	44.0	58.1	77.2	18.7															
	124.0	22.6	4181	2.5				23.4	41.3	54.6	72.5	17.6															
	118.5	23.6	3995	2.0				23.4	41.3	54.6	72.5	17.6															
	109.3	25.6	3685	2.8				23.4	41.3	54.6	72.5	17.6															
PL 10003	94.9	9.5	9954	0.8	15.0	10.5	160L6B	34.1	49.9	-	-	25.6	244	-	211	249	294	410-421									
	82.1	11.0	8611	1.1				32.5	47.5	-	-	24.4															
	75.2	12.0	7888	1.2				32.5	47.5	-	-	24.4															
	62.9	14.3	6598	1.4				30.6	44.7	-	-	22.9															
	57.6	15.6	6042	1.5				30.6	44.7	-	-	22.9															
	144.0	9.7	9710	0.9				15.0	10.5	160M4B	32.5	47.5							-	-	24.4	222	-	189	227	272	410-421
124.0	11.3	8361	1.0	32.5	47.5	-	-				24.4																
118.5	11.8	7990	0.8	32.5	47.5	-	-				24.4																
109.3	12.8	7370	1.1	31.5	46.1	-	-				23.6																
94.9	14.8	6399	1.2	30.6	44.7	-	-				22.9																
82.1	17.1	5536	1.6	28.9	42.3	-	-				21.7																
75.2	18.6	5071	1.7	28.9	42.3	-	-	21.7																			
62.9	22.3	4241	2.0	26.0	38.0	-	-	19.5																			
57.6	24.3	3884	2.1	25.4	37.1	-	-	19.0																			