



P1 (kW)		iges	n2 (rpm)	M2 (Nm)	fs	Pt (20°C) (kW)	Pt (40°C) (kW)	Motor IE2	FR (kN)					~ Kg															
									MC	MS	PC	PS	CPC	M...	P...	F	FS	CPC											
45.00	PL 50003*	170.1	8.2	46922	0.8				97.9	135.3	-	-	73.4	710	-	652	665	814	536-549										
		157.3	8.9	43391	0.8				93.5	129.2	-	-	70.1																
		130.2	10.8	35915	1.0				89.0	123.0	-	-	66.8																
		116.9	12.0	32247	1.1				86.3	119.3	-	-	64.7																
		108.0	13.0	29792	1.1	25.0	17.5	225M4D	86.3	119.3	-	-	64.7																
		93.0	15.1	25654	1.3				83.7	115.6	-	-	62.7																
		84.4	16.6	23282	1.9				83.7	115.6	-	-	62.7																
		74.2	18.9	20468	1.5				79.2	109.5	-	-	59.4																
		64.0	21.9	17654	2.4				71.2	98.4	-	-	53.4																
		53.1	26.4	14648	2.8				69.4	95.9	-	-	52.1																
		247.7	11.3	34164	1.0				89.0	123.0	-	-	66.8							665	-	607	620	769	536-549				
		205.5	13.6	28343	1.2				83.7	115.6	-	-	62.7																
		170.1	16.5	23461	1.4				83.7	115.6	-	-	62.7																
		157.3	17.8	21695	1.5				73.9	102.1	-	-	55.4																
138.6	20.2	19116	1.3	25.0	17.5	225M2B	73.9	102.1	-	-	55.4																		
130.2	21.5	17958	1.7				73.9	102.1	-	-	55.4																		
116.9	24.0	16123	1.9				69.4	95.9	-	-	52.1																		
108.0	25.9	14896	2.0				69.4	95.9	-	-	52.1																		
93.0	30.1	12827	2.3				65.9	91.0	-	-	49.4																		
74.2	37.7	10234	2.7				59.6	82.4	-	-	44.7																		
230.3	12.2	31764	0.8				72.0	102.0	-	-	54.0	533	-	497	505	596	516-529												
191.1	14.7	26357	0.9				67.7	95.9	-	-	50.8																		
164.1	17.1	22633	1.0				67.7	95.9	-	-	50.8																		
158.1	17.7	21806	1.0				59.8	84.7	-	-	44.8																		
136.2	20.6	18785	1.2				59.8	84.7	-	-	44.8																		
121.1	23.1	16703	1.3				56.2	79.6	-	-	42.1																		
108.7	25.8	14992	1.4	23.0	16.1	225M2B	56.2	79.6	-	-	42.1																		
99.6	28.1	13737	1.5				53.3	75.5	-	-	40.0																		
88.6	31.6	12220	2.0				53.3	75.5	-	-	40.0																		
83.2	33.7	11475	1.8				50.4	71.4	-	-	37.8																		
70.7	39.6	9751	2.4				48.2	68.3	-	-	36.2																		
64.8	43.2	8937	2.6				46.8	66.3	-	-	35.1																		
58.7	47.7	8096	2.8				46.1	65.3	-	-	34.6																		
53.7	52.1	7407	3.0				46.1	65.3	-	-	34.6																		
108.7	12.9	29985	0.8				69.8	98.9	-	-	52.4	578	-	542	550	641	516-529												
99.6	14.1	27474	0.9				67.7	95.9	-	-	50.8																		
88.6	15.8	24440	1.1				67.7	95.9	-	-	50.8																		
83.2	16.8	22951	1.0				64.1	90.8	-	-	48.1																		
70.7	19.8	19502	1.3	23.0	16.1	225M4D	59.8	84.7	-	-	44.8																		
64.8	21.6	17875	1.4				59.8	84.7	-	-	44.8																		
58.7	23.9	16192	1.6				56.2	79.6	-	-	42.1																		
53.7	26.1	14813	1.7				56.2	79.6	-	-	42.1																		
102.9	13.6	28385	0.8				43.7	66.4	-	-	32.7							572	-	531	539	635	496-509						
88.6	15.8	24440	0.9				42.3	64.4	-	-	31.7																		
73.5	19.0	20275	1.1				37.4	56.9	-	-	28.0																		
64.8	21.6	17875	1.2				37.4	56.9	-	-	28.0																		
134.4	20.8	18537	1.1				37.4	56.9	-	-	28.0													527	-	486	494	590	496-509
124.3	22.5	17144	1.2				35.1	53.4	-	-	26.3																		
102.9	27.2	14192	1.4	23.0	16.1	225M2B	35.1	53.4	-	-	26.3																		
88.6	31.6	12220	1.6				33.3	50.7	-	-	25.0																		
73.5	38.1	10137	1.9				30.2	45.9	-	-	22.6																		
64.8	43.2	8937	2.1				29.3	44.5	-	-	21.9																		
106.3	13.2	29323	0.8				43.7	66.4	-	-	32.7	541	-	505	513	602	476-489												
88.0	15.9	24275	0.9				42.3	64.4	-	-	31.7																		
73.1	19.2	20164	1.1	20.0	14.0	225M4D	37.4	56.9	-	-	28.0																		
60.5	23.1	16689	1.3				36.0	54.8	-	-	27.0																		
55.4	25.3	15282	1.3				35.1	53.4	-	-	26.3																		
156.0	17.9	21516	0.8				37.4	56.9	-	-	28.0							496	-	460	468	557	476-489						
134.3	20.8	18523	0.9				37.4	56.9	-	-	28.0																		
128.4	21.8	17709	1.2				37.4	56.9	-	-	28.0																		
114.4	24.5	15779	1.0				35.1	53.4	-	-	26.3																		
106.3	26.3	14661	1.4	20.0	14.0	225M2B	35.1	53.4	-	-	26.3																		
95.0	29.5	13103	1.2				33.3	50.7	-	-	25.0																		
88.0	31.8	12137	1.6				33.3	50.7	-	-	25.0																		
73.1	38.3	10082	1.9				30.2	45.9	-	-	22.6																		
60.5	46.3	8344	2.2				29.3	44.5	-	-	21.9																		
55.4	50.5	7641	2.4				28.8	43.8	-	-	21.6																		
PL 18003*	53.8	26.0	14841	0.8	17.0	11.9	225M4D	23.4	41.3	54.6	72.5	17.6	461	488	430	466	511							452-469					

* Soğutucu gereklidir / Cooling is required / Kühlung ist erforderlich / È richiesto raffreddamento / Le refroidissement est nécessaire / Se requiere un enfriamiento