

P1 (kW)		iges	n2 (rpm)	M2 (Nm)	fs	Pt (20°C) (kW)	Pt (40°C) (kW)	Motor IE2	FR (kN)					~ Kg									
									MC	MS	PC	PS	CPC	M...	P...	F	FS	CPC					
18.50	PL 50003	293.6	4.8	33295	0.9				120.2	166.1	-	-	90.1										
		247.7	5.7	28090	1.4				106.8	147.6	-	-	80.1										
		205.5	6.8	23305	1.6				102.4	141.5	-	-	76.8										
		170.1	8.2	19290	1.9				97.9	135.3	-	-	73.4										
		157.3	8.9	17838	2.0	25.0	17.5	180M4B	93.5	129.2	-	-	70.1	541	-	483	496	645	536-549				
		138.6	10.1	15718	1.8				89.0	123.0	-	-	66.8										
		130.2	10.8	14765	2.4				89.0	123.0	-	-	66.8										
		116.9	12.0	13257	2.6				86.3	119.3	-	-	64.7										
	108.0	13.0	12248	2.7				86.3	119.3	-	-	64.7											
	PL 50003	293.6	9.5	16648	1.7	25.0	17.5	160L/2C	89.0	123.0	-	-	66.8	507	-	449	462	611	536-549				
		247.7	11.3	14045	2.4				89.0	123.0	-	-	66.8										
		205.5	13.6	11652	2.9				83.7	115.6	-	-	62.7										
	PL 35003	191.1	4.7	33711	0.8				97.2	137.7	-	-	72.9										
		164.1	5.5	28948	1.0				97.2	137.7	-	-	72.9										
		158.1	5.7	27890	1.0				86.4	122.4	-	-	64.8										
		136.2	6.6	24027	1.1				82.8	117.3	-	-	62.1										
121.1		7.4	21363	1.2				82.8	117.3	-	-	62.1											
108.7		8.3	19175	1.4				79.2	112.2	-	-	59.4											
99.6		9.0	17570	1.4	23.0	16.1	200L/6B	75.6	107.1	-	-	56.7	452	-	416	424	515	516-529					
88.6		10.2	15630	1.9				72.0	102.0	-	-	54.0											
83.2		10.8	14677	1.7				72.0	102.0	-	-	54.0											
70.7		12.7	12472	2.3				67.7	95.9	-	-	50.8											
64.8		13.9	11431	2.4				67.7	95.9	-	-	50.8											
58.7		15.3	10355	2.7				67.7	95.9	-	-	50.8											
53.7	16.8	9473	2.8				67.7	95.9	-	-	50.8												
PL 35003	230.3	6.1	26117	1.0				86.4	122.4	-	-	64.8											
	191.1	7.3	21672	1.2				82.8	117.3	-	-	62.1											
	164.1	8.5	18610	1.4				75.6	107.1	-	-	56.7											
	158.1	8.9	17929	1.4				75.6	107.1	-	-	56.7											
	136.2	10.3	15446	1.6				72.0	102.0	-	-	54.0											
	121.1	11.6	13733	1.8	23.0	16.1	180M4B	72.0	102.0	-	-	54.0	409	-	373	381	472	516-529					
	108.7	12.9	12327	2.0				69.8	98.9	-	-	52.4											
	99.6	14.1	11295	2.1				67.7	95.9	-	-	50.8											
88.6	15.8	10048	2.7				67.7	95.9	-	-	50.8												
83.2	16.8	9435	2.4				64.1	90.8	-	-	48.1												
PL 35003	230.3	12.2	13058	1.9				72.0	102.0	-	-	54.0											
	191.1	14.7	10836	2.2				67.7	95.9	-	-	50.8											
	164.1	17.1	9305	2.5	23.0	16.1	160L/2C	67.7	95.9	-	-	50.8	375	-	339	347	438	516-529					
	158.1	17.7	8965	2.5				59.8	84.7	-	-	44.8											
	136.2	20.6	7723	2.8				59.8	84.7	-	-	44.8											
PL 30003	134.4	6.7	23709	1.1				51.8	78.8	-	-	38.8											
	124.3	7.2	21927	1.2				51.8	78.8	-	-	38.8											
	102.9	8.7	18152	1.4				47.3	71.9	-	-	35.4											
	88.6	10.2	15630	1.6	23.0	16.1	200L/6B	45.0	68.5	-	-	33.8	446	-	405	413	509	496-509					
	73.5	12.2	12966	1.8				45.0	68.5	-	-	33.8											
64.8	13.9	11431	2.0				42.3	64.4	-	-	31.7												
PL 30003	134.4	10.4	15242	1.6				45.0	68.5	-	-	33.8											
	124.3	11.3	14096	1.7				45.0	68.5	-	-	33.8											
	102.9	13.6	11669	2.0				43.7	66.4	-	-	32.7											
	88.6	15.8	10048	2.2	23.0	16.1	180M4B	42.3	64.4	-	-	31.7	403	-	362	370	466	496-509					
	73.5	19.0	8335	2.6				37.4	56.9	-	-	28.0											
64.8	21.6	7349	2.9				37.4	56.9	-	-	28.0												
PL 30003	134.4	20.8	7621	2.8	23.0	16.1	160L/2C	37.4	56.9	-	-	28.0	369	-	328	336	432	496-509					
	124.3	22.5	7048	3.0				35.1	53.4	-	-	26.3											
PL 25003	156.0	5.8	27519	0.8				54.0	82.2	-	-	40.5											
	134.3	6.7	23691	0.8				51.8	78.8	-	-	38.8											
	128.4	7.0	22651	1.1				51.8	78.8	-	-	38.8											
	114.4	7.9	20181	1.0				49.5	75.4	-	-	37.1											
	106.3	8.5	18752	1.3				49.5	75.4	-	-	37.1											
	95.0	9.5	16759	1.1	20.0	14.0	200L/6B	47.3	71.9	-	-	35.4	415	-	379	387	476	476-489					
	88.0	10.2	15524	1.6				45.0	68.5	-	-	33.8											
	73.1	12.3	12895	1.8				45.0	68.5	-	-	33.8											
	60.5	14.9	10673	2.1				42.3	64.4	-	-	31.7											
	55.4	16.2	9773	2.3				42.3	64.4	-	-	31.7											