



P1 (kW)		iges	n2 (rpm)	M2 (Nm)	fs	Pt (20°C) (kW)	Pt (40°C) (kW)	Motor IE2	FR (kN)					~Kg					
									MC	MS	PC	PS	CPC	M...	P...	F	FS	CPC	
11.00	PLB 18003	163.3	8.6	11011	1.1	17.0	11.9	160M/4B	31.5	55.7	73.5	97.7	23.6	268	295	237	273	318	452-469
		135.5	10.3	9137	1.5				30.0	53.0	70.0	93.0	22.5						
		116.7	12.0	7869	1.5				30.0	53.0	70.0	93.0	22.5						
		103.3	13.6	6965	1.7				28.2	49.8	65.8	87.4	21.2						
		85.7	16.3	5779	2.3				28.2	49.8	65.8	87.4	21.2						
	71.2	19.7	4801	2.6	24.9	44.0	58.1	77.2	18.7										
	PLB 18003	163.3	17.1	5506	2.1	17.0	11.9	160M/2B	28.2	49.8	65.8	87.4	21.2	261	288	230	266	311	452-469
		135.5	20.7	4568	2.7				24.9	44.0	58.1	77.2	18.7						
		116.7	24.0	3935	2.7				23.4	41.3	54.6	72.5	17.6						
	103.3	27.1	3483	3.0	23.4	41.3	54.6	72.5	17.6										
	PLB 16003	140.0	6.4	14685	0.9	15.0	10.5	160L/6B	36.0	63.6	84.0	111.6	27.0	284	311	253	289	334	428-445
		125.8	7.2	13195	0.8				34.5	61.0	80.5	107.0	25.9						
		120.6	7.5	12650	1.0				34.5	61.0	80.5	107.0	25.9						
		116.1	7.8	12178	0.8				33.0	58.3	77.0	102.3	24.8						
96.2		9.4	10090	1.2	31.5				55.7	73.5	97.7	23.6							
88.8		10.1	9314	1.3	30.0				53.0	70.0	93.0	22.5							
76.5		11.8	8024	1.5	30.0				53.0	70.0	93.0	22.5							
61.1		14.7	6409	1.8	28.2				49.8	65.8	87.4	21.2							
50.7		17.8	5318	2.4	24.9				44.0	58.1	77.2	18.7							
46.4		19.4	4867	2.6	24.9				44.0	58.1	77.2	18.7							
PLB 16003	182.9	7.7	12333	0.8	15.0	10.5	160M/4B	33.0	58.3	77.0	102.3	24.8	262	289	231	267	312	428-445	
	157.5	8.9	10620	0.9				31.5	55.7	73.5	97.7	23.6							
	140.0	10.0	9440	1.3				30.0	53.0	70.0	93.0	22.5							
	125.8	11.1	8483	1.1				30.0	53.0	70.0	93.0	22.5							
	120.6	11.6	8132	1.5				30.0	53.0	70.0	93.0	22.5							
	116.1	12.1	7829	1.2				30.0	53.0	70.0	93.0	22.5							
	96.2	14.6	6487	1.8				28.2	49.8	65.8	87.4	21.2							
	88.8	15.8	5988	1.9				28.2	49.8	65.8	87.4	21.2							
	76.5	18.3	5158	2.2				24.9	44.0	58.1	77.2	18.7							
	61.1	22.9	4120	2.6				23.4	41.3	54.6	72.5	17.6							
PLB 16003	266.4	10.5	8982	0.8	15.0	10.5	160M/2B	30.0	53.0	70.0	93.0	22.5	255	282	224	260	305	428-445	
	221.0	12.7	7451	1.2				28.2	49.8	65.8	87.4	21.2							
	182.9	15.3	6166	1.4				28.2	49.8	65.8	87.4	21.2							
	157.5	17.8	5310	1.6				24.9	44.0	58.1	77.2	18.7							
	140.0	20.0	4720	2.3				24.9	44.0	58.1	77.2	18.7							
	125.8	22.3	4241	1.9				24.9	44.0	58.1	77.2	18.7							
	120.6	23.2	4066	2.6				23.4	41.3	54.6	72.5	17.6							
	116.1	24.1	3914	2.1				23.4	41.3	54.6	72.5	17.6							
PLB 10003	96.2	9.4	10090	0.8	15.0	10.5	160L/6B	34.1	49.9	-	-	25.6	276	-	244	281	326	410-421	
	88.8	10.1	9314	0.9				32.5	47.5	-	-	24.4							
	73.1	12.3	7667	1.2				32.5	47.5	-	-	24.4							
	61.1	14.7	6409	1.2				30.6	44.7	-	-	22.9							
	50.7	17.8	5318	1.6				27.0	39.4	-	-	20.2							
	46.4	19.4	4867	1.8				27.0	39.4	-	-	20.2							
PLB 10003	140.0	10.0	9440	0.9	15.0	10.5	160M/4B	32.5	47.5	-	-	24.4	254	-	222	259	304	410-421	
	125.8	11.1	8483	0.8				32.5	47.5	-	-	24.4							
	120.6	11.6	8132	1.0				32.5	47.5	-	-	24.4							
	116.1	12.1	7829	0.8				32.5	47.5	-	-	24.4							
	96.2	14.6	6487	1.2				30.6	44.7	-	-	22.9							
	88.8	15.8	5988	1.3				30.6	44.7	-	-	22.9							
	73.1	19.2	4929	1.7				27.0	39.4	-	-	20.2							
	61.1	22.9	4120	1.7				25.4	37.1	-	-	19.0							
	50.7	27.6	3419	2.4				24.1	35.2	-	-	18.0							
	46.4	30.2	3129	2.5				24.1	35.2	-	-	18.0							
PLB 10003	221.0	12.7	7451	0.8	15.0	10.5	160M/2B	30.6	44.7	-	-	22.9	247	-	215	252	297	410-421	
	182.9	15.3	6166	1.0				30.6	44.7	-	-	22.9							
	157.5	17.8	5310	1.1				27.0	39.4	-	-	20.2							
	140.0	20.0	4720	1.5				27.0	39.4	-	-	20.2							
	125.8	22.3	4241	1.3				27.0	39.4	-	-	20.2							
	120.6	23.2	4066	1.8				25.4	37.1	-	-	19.0							
	116.1	24.1	3914	1.4				25.4	37.1	-	-	19.0							
	96.2	29.1	3243	2.1				24.1	35.2	-	-	18.0							
88.8	31.5	2994	2.3	24.1	35.2	-	-	18.0											
PLB 7003	55.6	16.2	5832	0.8	14.0	9.8	160L/6B	-	-	54.1	64.9	40.5	-	216	198	219	233	392-403	
	53.6	16.8	5622	0.8				-	-	54.1	64.9	40.5							
PLB 7003	77.9	18.0	5253	0.9	14.0	9.8	160M/4B	-	-	47.7	57.3	35.8	-	194	176	197	211	392-403	
	67.1	20.9	4525	1.0				-	-	47.7	57.3	35.8							
	60.5	23.1	4079	0.9				-	-	44.9	53.8	33.6							
	55.6	25.2	3749	1.1				-	-	44.9	53.8	33.6							
53.6	26.1	3614	1.2	-	-	44.9	53.8	33.6											